



# ICT International

## **Product Support Documentation**

**Version:** 2.6.1

**Release Date:** March 2026

# About this document

---

## Version information

Document code/Version	Date	Description

## Related manuals

Product Code	Product Name	Brief description

## Documentation conventions

### **WARNING**

Dangerous certain consequences of an action.

### **CAUTION**

Negative potential consequences of an action.

### **IMPORTANT**

Essential information required for user success.

### **NOTE**

Information the user should notice even if skimming.

**TIP**

Optional information to help a user be more successful.

## Product overview

---

The Psychrometer is

### Functional description

Inputs: Sensor

### Components (what's in the box)

---

Included with the

### Optional features

Options include:

-

### USB cables

### Installation Kit

Plain Text

### Config Tool

Plain text

### Backward compatibility

Plain text

### ESD Protection

**CAUTION**

- Negative potential consequences of an action.

Plain Text

# Functional Description

Plain Text

## Measurement principle

Plain Text

## Inputs

Plain text

## Outputs

Plain text

# Installation

Plain text

### **TIP**

- Optional information to help a user be more successful.

## Site Selection

Plain text

## Unpacking

Plain text

## Installing

Plain text

## Placing

Plain text

## Mounting

Plain text

## Aligning

Plain text

## Configuring offset

Plain text

## Installing Configuration Tool

Plain Text

## Installing USB cable driver

Plain text

## Powering the sensor/ instrument/ device

Plain text

## Power supplies

Plain text

## Power management

Plain text

## Wiring

Plain text

## Solar

Plain text

## Connections

Plain text

## Comm options

Plain text

## Comm protocols

Plain text

## Connection cables

Plain text

# Communications Settings

Plain text

# Commands

Plain text

# SDI-12

Plain text

# RS-485

Plain text

# Analogue

Plain text

# Settings

Plain text

# Checking the settings

Plain text

# Setting fields

Plain text

# Changing the settings

Plain text

# Maintenance

Plain text

# Cleaning

Plain text

# Calibration

Plain text

# Troubleshooting

Plain text

## Error messaging

Plain text

## Missing readings and error indication

Plain text

## Technical specifications

Plain text

## Specifications

Plain text

## Options and accessories

Plain text

## Networking

Plain text

## Connecting several sensors

Plain text

## SDI-12

Plain text

## RS-485

Plain text

## Analogue

Plain text

## Decoder

Plain text

## External sensors

Plain text

# Complimenting sensors

Plain text

not change any of the LoRaWAN key settings unless you are changing the gateway connection of the device.

- Changes made to LoRaWAN keys will require reprogramming at the LoRaWAN Server

## ⊗ IMPORTANT

### Site Selection:

When choosing the site for the device installation, consideration must be given to:

- Gateway location
- Node positioning
- Antenna orientation
- Obstructions between the node and gateway

## Installation location

The installation location of the AD-Node is determined by:

- Signal strength
- Sensor positions
- Cable lengths

## Positioning of the AD-Node

Position the AD-Node towards the LoRaWAN gateway to optimise the signal.

Ensure that there are no obstructions within the following distances:

<b>LoRaWAN Frequency</b>	<b>Whole wavelength in centimetres</b>	<b>Minimum distance to obstruction</b>
EU868 (Europe)	34.5	17 cm
AU915 (Australia)	32.7	16 cm
US915 (United States)	32.7	16 cm
AS923 (Asia)	32.4	16 cm

# Mounting the AD-Node

Included with the AD-Node are 4 brackets that can be screwed to the rear of the node enclosure using the moulded holes in the corners. These can be used to mount the node enclosure wall or post.

# Powering the device

The AD-Node is a self-powered device with 3x AA batteries. It is recommended to use 1.5-volt lithium batteries when replacements are needed. The supplied AA batteries are L91 Energizer single use batteries, mAh, 1.5 volt.

To power the device on, move the switch to the On position.

The unit will start to transmit at the logging interval from the moment it is powered on. This is confirmed by the LED light sequence:

Red, blue sparkles

# Connecting sensors

The AD-Node is supplied with sensors connected. If the sensors need to be disconnected (e.g. for running cables through conduit) then the following needs to be followed.

Each connector in the enclosure is almost tool-less for installation, with a push to fit connector.

To release the cable, a jeweller's flat head screwdriver is required.

# Configuration Changes

---

## Communication Settings

Any changes that are needed to be made, such as measurement frequency, can be made using the node terminal function.

Node Terminal is downloadable from:

## Checking the settings

Settings can be checked using Node Terminal

## ⊗ CAUTION

- Do not change any of the LoRaWAN key settings unless you are changing the gateway connection of the device.
- Changes made to LoRaWAN keys will require reprogramming at the LoRaWAN Server

## Setting LoRaWAN fields

The settings fields that can be changed are:

- LoRaWAN Keys
- Sensor/Measurement Settings

## Changing the LoRa settings

To retrieve or reprogram LoRaWAN keys (OTAA), enter the following:

<b>To Retrieve:</b>	<b>To Reprogram:</b>
lora eui dev	lora eui dev 0011223344556677
lora eui app	lora eui app 0011223344556677
lora key app	lora key app 00112233445566778899887766554433

<b>To Retrieve:</b>	<b>To Reprogram:</b>
lora eui dev	lora eui dev 0011223344556677
lora eui app	lora eui app 0011223344556677
lora key app	lora key app 00112233445566778899887766554433

## Sensor Settings

### Changing the measurement frequency

The upload schedule can be changed using the command report period. By default the system will be shipped at a 10-minute logging interval (600).

e.g. changing to a 15-minute interval would use the following code:

report period 900

## Analogue Configuration

Analogue measurements can be post-processed in the cloud

## Maintenance

---

Maintenance is at the sensor level, rather than the device level.

The batteries are replaceable. To replace follow the steps below:

- Open the enclosure
- Turn the power off by moving the switch to the 1 position
- Release the battery retaining strap
- Remove the batteries
- Check the polarity of the new batteries
- Insert the batteries
- Replace the retaining strap
- Turn the device switch to the On position
- Clean the rubber seal and opposite surface
- Close the enclosure, and ensure that both latches are fully closed

## Calibration

There is no calibration of the device available.

Calibration is undertaken on a sensor-by-sensor basis.

## Troubleshooting

---

Plain text

## Error messaging

Plain text

## Missing readings and error indication

Plain text

## Technical specifications

---

*All technical specifications are subject to change as the products undergo continuous improvement*

# Specifications

	<b>Detail</b>
Analogue	Analogue inputs with selectable voltage  0 - 12v Input Range  4x Single Ended or 2x Differential
Digital	Digital inputs with pulse counting  Up to 1kHz input frequency
Operating Environment	-20°C to 60°C
Enclosure Dimensions:	IP65 Clam-Shell 140 ×120 ×80 mm, 500 g
Certifications:	AS/NZS 60950.1:2011  AS/NZS 4268:2012  RoHS compliant (lead-free)

## Options and accessories

Plain text

## Compatible sensors

<b>Product Code</b>	<b>Product Name</b>	<b>Maximum possible number*</b>
MP406		
DBV60		
DPV40		
SMT100a		
Therm-EP		
PRP-02		

\* this is the maximum number of that sensor that can on an individual node. Combinations will be different.